

zenith<sup>o</sup>

# Zenith Filter Tap

Under-sink filtered water

**Filtered drinking water**



## **Features**

**Fresh, filtered water at the touch of a tap**

**More cost effective than buying bottled water**

Convenient with no bottles to store or jugs to fill

Easy under the sink installation

Quick and hygienic filter change

***Backed by the Zenith nationwide service network***

See installation instructions for warranty details.

*Zenith Spec Sheets Update: 010608*

**Features**

- Fresh, filtered ambient water at the touch of a tap.
- More cost effective than buying bottled water.
- Modern design swivel head with easy lever action tap.
- Easy under the sink installation.
- Quick and easy change filter system.
- Equipped with a pressure limiting device to prevent water hammer which can damage filter cartridges causing leaks or improper filtration.

**Sink mounted tap**

Chrome plate brass with quarter turn action tap and swivel spout mounted near the edge of the sink so that it drains into the sink when running.

**Under-sink filtration**

Available in choice of 5-star rated 5 micron or Sub micron filtration.  
Filter maximum flow rate is 2 litres per minute.

**Installation**

**Location**

The tap should be positioned at rear of a sink. The tap should be mounted on a flat surface. A 25mm diameter cut-out is required for fitting. Filter should be mounted under the sink on the cupboard wall close to the tap.

**Plumbing**

Water connections 12.7 mm BSP. Designed for direct connection to a potable cold water supply with a minimum pressure of 70kPa and a maximum pressure of 700kPa.

**Note**  
To be installed by a qualified tradesperson in accordance with manufacturer's instructions and AS/NZS 3500 plumbing and AS/NZS 3350 wiring regulations.

**Technical Advice**  
Contact Zenith Heaters Limited on **0800 558 055**.

**Accessories**  
52000NZ – 5 micron filter\*  
58000NZ – Sub micron filter\*  
\*Zenith filters comply with NSF/ANSI 42 and/or 53 industry standards.

| Product Details                  | Order code Model No. for 5 micron filter | Order code Model No. for Sub micron filter |
|----------------------------------|--|--|
| Filter Tap (Ambient Temperature) | 52007NZ                                  | 59007NZ                                    |

