

zenith^o

Automatic Hand Dryers

Touch-Free Hand Dryers



SuperDry 20000NZ.



SuperDry Extreme 20012NZ.

Features

Infrared activated hand dryers

Improves washroom hygiene

Robust and easy to use

Choice of three models

Energy efficient design

Warm air recycling technology speeds up drying

Easy to install

Saves paper

Concealed power cord if required

Backed by the Zenith nationwide service network

See installation instructions for warranty details.

Zenith Spec Sheets Update: 010608



zenith°

Automatic Hand Dryers

Touch-Free Hand Dryers

Features

- Automatic hand dryers for convenience and hygiene.
- Operates automatically by infrared electronic sensor to provide rapid drying.
- Bi-directional flap directs air downwards for hand drying or upwards for face drying on SuperDry Standard and Extreme models only.
- For safety reasons or in case of obstruction, automatic cut-out protection to heating element and motor fan if used continuously for 60 seconds.
- Automatic cut-out protection to heating element and motor fan.
- Cushion mounting isolators to minimise operating noise level.

Fan

Electronically balanced pressed metal for SuperDry Extreme.

Nylon fan for SuperDry Standard and Magic Eye models.

Motor

Sealed ball bearing motor with thermal protection.

Air volume

52 Litres per second.

Stop/start

Infrared electronic sensor.

Overheat

Cuts out if thermally overloaded.

Cut-out and Reset

Cuts out after 60 seconds if sensor is obstructed. Automatically resets when obstruction removed.

Technical Details SuperDry Extreme

Element: 2.2kW protected by 120°C cut out.
 Electrical: 220 - 240 V, 50 Hz, 9.8 amps.
 Stop/start: infrared electronic sensor.
 Case: die cast aluminium.
 Colour: Silver.

Technical Details SuperDry Standard

Element: 2.2kW protected by 100°C cut out.
 Electrical: 220 - 240 V, 50 Hz, 9.8 amps.
 Stop/start: Infrared electronic sensor.
 Case: Die cast aluminium.
 Colour: White.

Installation

To be connected to a 10amp GPO, 220V - 240V AC power supply.

The dryer should be positioned on a wall at a suitable height as indicated on adjoining table and within 900mm of electrical wiring GPO.

Zenith recommended distance from dryer to base of floor:

Mens washroom	1065 mm
Ladies washroom	1015 mm
Child washroom 13–17 years	1015 mm
Child washroom 10–13 years	915 mm
Child washroom 7–10 years	865 mm
Child washroom 4–7 years	760 mm
Disabled washroom	800 mm

Note

To be installed by a qualified tradesperson in accordance with manufacturer's instructions and AS/NZS 3500 plumbing and AS/NZS 3350 wiring regulations.

Technical Advice

Contact Zenith Heaters Limited on **0800 558 055**.

Product Details	Order Code	Power	Airflow Rate litres/sec	Weight kgs	Casing	Dimensions		
						A	B	C
SuperDry Extreme	20012NZ	2.2kW	52	8	Silver Die Cast Aluminium	326	254	188
SuperDry Standard	20000NZ	2.2kW	52	4	White Die Cast Aluminium	287	252	185

